# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 1 / 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

automatic transmission fluid (ATF) Article number: 08971, 30017

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Gearbox oil

1.2.2 Uses advised against

For all uses not specified in SECTION 1.2.1

### 1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictogramsnoneSignal wordnoneHazard statementsnonePrecautionary statementsnone

**Special labelling** EUH210 Safety data sheet available on request.

2.3 Other hazards

**Human health dangers** If swallowed or in the event of vomiting, risk of product entering the lungs.

Frequent persistent contact with the skin can cause skin irritation.

Other hazards No particular hazards known.

# **SECTION 3: Composition / Information on ingredients**

### 3.1 Substances

not applicable

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

#### Page 2 / 12

#### 3.2 Mixtures

#### The product is a mixture.

Range [%]	Substance
30 - < 60	Distillates (petroleum), hydrotreated light paraffinic
	CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2.5	Base oil
	CAS: 72623-86-0, EINECS/ELINCS: 276-737-9, Reg-No.: 01-2119474878-16-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2.5	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2.5	Methacrylate copolymer
	EINECS/ELINCS: Polymer
	GHS/CLP: Eye Irrit. 2: H319

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**General information** Take off contaminated clothing and wash before reuse.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

**Skin contact** When in contact with the skin, clean with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Seek medical advice immediately.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.

Forward this sheet to your doctor.

### **SECTION 5: Fire-fighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide.

Dry powder. Foam.

Extinguishing media that must not

be used

Full water jet.

#### 5.2 Special hazards arising from the substance or mixture

Not combusted hydrocarbons.

Risk of formation of toxic pyrolysis products.

Sulphur oxides (SOx). Nitrogen oxides (NOx).

# ebi bilstein

Page 3 / 12

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

#### 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.

Forms slippery surfaces with water.

### 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

#### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

#### 6.4 Reference to other sections

See SECTION 8+13

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Avoid formation of aerosols.

The product is combustible.

Fire class (DIN EN 2): B

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Wash hands before breaks and after work.

Cloths contaminated with product should not be kept in trouser pockets.

Take off contaminated clothing and wash before reuse.

Contaminated work clothing should not be allowed out of the workplace.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with food and animal food/diet.

Do not store together with oxidizing agents.

Keep container tightly closed.

Keep container in a well-ventilated place.

Protect from heat/overheating.

# 7.3 Specific end use(s)

See product use, SECTION 1.2



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 4 / 12

# SECTION 8: Exposure controls / personal protection

### 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Distillates (petroleum), hydrotreated light paraffinic

CAS: 64742-55-8, EINECS/ELINCS: 265-158-7, EU-INDEX: 649-468-00-3, Reg-No.: 01-2119487077-29-XXXX

Long-term exposure: 5 mg/m³, ACGIH TLV (OIL MIST)

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX

Long-term exposure: 5 mg/m³, oil mist

Short-term exposure (15-minute): 10 mg/m<sup>3</sup>

#### **DNEL**

Substance		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³		
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³		
general population, oral, Long-term - systemic effects, 740 µg/kg bw/day		
general population, inhalative, Long-term - local effects, 1.19 mg/m³		
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8		
Industrial, dermal, Long-term - systemic effects, 0.97 mg/kg bw/day		
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³		
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³		
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day		

#### **PNEC**

Substance		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
oral (food), 9.33 mg/kg		
Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8		
oral (food), 9.33 mg/kg food		

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 5 / 12

#### 8.2 Exposure controls

Additional advice on system design 
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

General exposure limit for oil mist should be noted.

**Eye protection** Safety glasses. (EN 166:2001)

**Hand protection** The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0.4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3). > 0.4 mm: Neoprene, >480 min (EN 374-1/-2/-3).

**Skin protection** light protective clothing

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

**Respiratory protection** Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards none

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical stateliquidFormliquidColorredOdormild

Odour threshold No information available.

pH-value not applicable
pH-value [1%] not applicable
Boiling point [°C] not applicable
Flash point [°C] > 160 (DIN ISO 2592)

Flammability (solid, gas) [°C]

No information available.

No information available.

Upper explosion limit

No information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] < 0.01 (20°C)

**Density [g/cm³]** ca. 0.854 (DIN 51757) (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water immiscible

Solubility other solvents No information available.

Partition coefficient [n-octanol/water] No information available.

Kinematic viscosity ca. 38 mm<sup>2</sup>/s (40°C) (DIN 51562/T1)

7.1 mm<sup>2</sup>/s (100°C)

Relative vapour densityNo information available.Evaporation speedNo information available.Melting point [°C]No information available.

Auto-ignition temperature not applicable

Decomposition temperature [°C] > 65

Particle characteristics No information available.

# ebi bilstein

### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 6 / 12

#### 9.2 Other information

Drop point: ca. -40°C

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No dangerous reactions known if used as directed.

### 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

### 10.3 Possibility of hazardous reactions

Reactions with oxidizing agents. Reactions with acids.

### 10.4 Conditions to avoid

Strong heating.

Decomposes begins at > 65°C °C.

#### 10.5 Incompatible materials

Oxidizing agent

# 10.6 Hazardous decomposition products

No hazardous decomposition products known.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 7 / 12

### **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

Product

oral, Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, oral, Rat, 5000 mg/kg bw

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LD50, oral, Rat, 5000 mg/kg bw

Base oil, CAS: 72623-86-0

LD50, oral, Rat, > 2001 mg/kg

#### Acute dermal toxicity

Product

dermal, Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit, 2000 - 5 00 mg/kg bw

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LD50, dermal, Rabbit, 2000 - 5000 mg/kg bw

Base oil, CAS: 72623-86-0

LD50, dermal, Rabbit, > 2001 mg/kg

### Acute inhalational toxicity

Product

inhalative, Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h

Base oil, CAS: 72623-86-0

LC50, inhalative, Rat, > 5.53 mg/l/4h

Serious eye damage/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

Eye, non-irritating

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

dermal, non-irritating



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 8 / 12

Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

dermal, non-sensitizing

Specific target organ toxicity — single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m3 air

LOAEL, oral, Rat, 125 mg/kg bw/day

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

NOAEC, inhalative, Rat, 980 mg/m³ (subacute), no adverse effect observed

LOAEL, dermal, mouse, 100 mg/kg bw/day (chronic), The effects observed are not sufficient for classification.

LOAEL, oral, Rat, 125 mg/kg bw/day, The effects observed are not sufficient for classification.

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

in vitro, negativ

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

- Fertility

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed, Effect on fertility

- Development

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed, Effect on fertility,

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard General remarks Based on the available information, the classification criteria are not fulfilled.

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 9 / 12

#### 11.2 Information on other hazards

Endocrine disrupting properties No information available.

Other information none

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product

Based on the available information, the classification criteria are not fulfilled.

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

EL50, (48h), Invertebrates, 10 g/L

NOELR, (14d), fish, 1 mg/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), fish, 100 mg/L

Distillates (petroleum), hydrotreated light paraffinic, CAS: 64742-55-8

NOELR, (14d), fish, 1 g/L

LL50, (96h), Invertebrates, 10 g/L

LL50, (96h), fish, 100 mg/L

#### 12.2 Persistence and degradability

Behaviour in environment

compartments

No information available.

Behaviour in sewage plant No information available.

Biological degradability The product is only slightly biodegradable.

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

### 12.6 Endocrine disrupting properties

No information available.

#### 12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 10 / 12

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**Product** 

In according to RoHS!

Coordinate disposal with the authorities if necessary.

Waste no. (recommended)

130205\* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102 150104

150110\* packaging containing residues of or contaminated by hazardous substances

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

**IMDG** 

not applicable

Air transport in accordance with IATA not applicable

### 14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

**IMDG** 

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

#### 14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with

IMDG

not applicable

Air transport in accordance with IATA not applicable

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0

Page 11 / 12

#### 14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with

**IMDG** 

not applicable

Air transport in accordance with IATA not applicable

#### 14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with no

**IMDG** 

Air transport in accordance with IATA no

#### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

# 14.7 Maritime transport in bulk according to IMO instruments

not applicable

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**EEC-REGULATIONS** 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

TRANSPORT-REGULATIONS ADR (2023); IMDG-Code (2023, 41. Amdt.); IATA-DGR (2023)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

no

- VOC (2010/75/CE) 0%

# 15.2 Chemical safety assessment

not applicable

#### **SECTION 16: Other information**

### 16.1 Hazard statements (SECTION 3)

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 24.01.2023, Revision 24.01.2023

Version 11.0. Supersedes version: 10.0 Page 12 / 12

#### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level EC50 = Median effective concentration

ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average

TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

# 16.3 Other information

Classification procedure

Modified position none

bfe00029