

10080300

R010624

VOLVO



GASOLINA

(mm)



(mm)

c.c. 1596

(cm3)

78

(mm)

1

B16F

1

81003000

M12X1.50X111(10)

1

- 1) 3 Kpm
- 2) 50°
- 3) -180°
- 4) 2.5 Kpm

5) 123°



(Kp.m)

1

NO

RETIGHTENING

ROUGHNESS



MLS



ALUMINIUM
ALUMINIO
CAST IRON
FUNDICIÓN

0.5 / 1.0 µm
1.5 / 1.8 µm

2.3 µm MAX
3.8 µm MAX

-90° +

-180°

< >

LOOSEN ROT AND TIGHTEN BOLT BY BOLT RESPECTING THE SPECIFIED TORQUE AND ORDER

AFLOJAR ROT Y APRETAR TORNILLO A TORNILLO CON EL PAR Y ORDEN ESPECIFICADOS

LOOSEN ALL THE BOLTS

AFLOJAR TODOS LOS TORNILLOS

RUN THE ENGINE UNTIL TOTAL OPENING OF THE THERMOSTAT

LET THE ENGINE COOL DOWN FOR 4 HOURS (WITH OPEN BONNET)

OPEN THE CAP OF THE EXPANSION TANK OF THE WATER COOLING CIRCUIT

RODAR EL MOTOR HASTA LA APERTURA TOTAL DEL TERNOSTATO

DEJAR ENFRIAR EL MOTOR CUATRO HORAS (CAPOT ABIERTO)

ABRIR EL TAPON DEL VASO DE EXPANSION DEL CIRCUITO DEL AGUA DE REFRIGERACION

1

- 1) 22 lbft
- 2) 50°
- 3) -180°
- 4) 18 lbft