



FUEL LINE HOSE

PRODUCT TYPE: FUEL SYSTEM

RECOMMENDED FOR: Clamped hose applications on all fuel systems, including fuel injection systems. Specially designed for fuel circuits (leaded and unleaded petrol, diesel) in passenger cars. Approved for transportation of B-7, E-5, E-10, E-15, low sulfur diesel.

RESISTANT TO: Tube resists heat and oil. Cover resists heat, oil, ozone and weathering.

CONSTRUCTION:
SHAPE: Straight
TUBE: Nitrile (NBR)
REINFORCEMENT: Textile
WIRE: -
COVER: Nitrile (NBR) / PVC

STANDARDS:
SAE NORM SAE J30R7
DIN NORM DIN 73379, except tolerances



TEMPERATURE:

| | PN | | | | | | | | |
|----------|-------------|-----|-------|----|----|-----|-----|-----|-------|
| | | mm | " | mm | m | mm | bar | bar | mm/HG |
| FL3.2X15 | 3225-00050 | 3.2 | 7/64 | 8 | 15 | 71 | 7.5 | 30 | 608 |
| FL4X15 | 3225-00051 | 4 | 5/32 | 9 | 15 | 75 | 7.5 | 30 | 608 |
| FL5X15 | 3225-00055 | 5 | 13/64 | 10 | 15 | 76 | 7.5 | 30 | 608 |
| FL6X15 | 3225-00052 | 6 | 1/4 | 12 | 15 | 79 | 7.5 | 30 | 608 |
| FL7X15 | 3225-00056 | 7 | 9/32 | 13 | 15 | 89 | 7.5 | 30 | 608 |
| FL8X15 | 3225-00053 | 8 | 5/16 | 14 | 15 | 91 | 7.5 | 30 | 608 |
| FL10X10 | 3225-00054 | 10 | 3/8 | 16 | 10 | 114 | 7.5 | 30 | 608 |
| FL10X15 | 3225-10014* | 10 | 3/8 | 16 | 15 | 114 | 7.5 | 30 | 608 |
| FL12X15 | 3225-10015* | 12 | 15/32 | 19 | 15 | 127 | 7.5 | 30 | 608 |

* boxed, not reeled