

THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1227*00

Reason for extension:

SECTION I

0.1 Make (trade name of manufacturer) : Le Rapide

0.2. Type and general commercial description(s) : 023641 → 026061

0.3. Means of identification of type

marked on the component : Approval number

0.3.1. Location of the marking : on type plate

0.5. Name and address of manufacturer : Bosal Le Rapide

Rue de Reims

F-51490 Beine Nauroy France

0.7. In the case of components and separate technical units, location and method of affixing of the EEC approval mark

: on type plate

0.8. Name(s) and address(es) of assembly plants : See information document

(annex III, item 0.8)

wp5169c.r00/1:3/e

SECTION II

1. Additional information (where applicable)

: see Appendix I

2. Technical service responsible for

carrying out the tests

: RDW

Testbaan|Centrum Talingweg 76 8218 NX Lelystad

3. Date of testreport

: 22-12-1998

4. Number of testreport

: RDW-94/20-0202

5. Remarks (if any)

: see Appendix I

6. Place

: Zoetermeer

- 7. Date
- 8. Signature

- B. Bysterbosch
- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*1227*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.	Additional information	•	
1.1.	Class of the type of coupling	: A50-X	
1.2.	Categories or types of vehicles for which the device is designed or restricted	: Peugeot 406 Restyling 4 doors	
1.3.	Maximum D-value	: 8,54	kN
1.4.	Maximum vertical load S at the coupling point	: 80	kg
1.5.	Maximum load U at the fifth wheel coupling point	:	ton
1.6.	Maximum V-value	:	kN
1.7.	Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles	: see fitting inst	ructions
1.8.	Information on the fitting of special towing brackets or mounting plates	: see fitting instructions	
_	D 1		

: The installation of the coupling device to the vehicle must be checked according to

requirements of Annex VII, see Annex I, par.5.10.

Remarks

5.