

NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1496*00

Reason for extension:

SECTION I

0.1. Make (trade name of manufacturer) : Bosal

0.2. Type and general commercial description(s) : 026211

0.3. Means of identification of type marked on the : Approval number component

0.3.1. Location of that marking : On type plate

0.5. Name and address of manufacturer : Bosal postbus 168

4920 AD Made Nederland

0.7. In the case of components and separate technical: On type plate

units, location and method of

affixing of the EEC type approval mark

0.8. Address(es) of assembly plant(s) : See information document

(annex III, item 0.8)

Type-approval number: e4*94/20*1496*00

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

: RDW

Testbaan|Centrum

Talingweg 76

8218 NX Lelystad

3. Date of test report

Date of test report

: 06-02-2001

4. Number of test report

: RDW-94/20-1500

5. Remarks (if any)

: See Appendix I

6. Place

: Zoetermeer

7. Date

: 06-02-2001

8. Signature

D.G. Burger

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*1496*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

| 1. | Additional | information |
|-----|---------------|--------------------|
| ~ • | 1 10011101101 | TTTT OT TITM CLOSE |

| 1.1. | Class of the type of coupling | A50-X |
|------|-------------------------------|-------------------------|
| | Class of the type of coupling | $\Delta J U - \Delta I$ |

| 1.2. | Categories or types of vehicles for which | : | See fitting instructions |
|------|---|---|--------------------------|
| | the device is designed or restricted | | - , |

| 1.3. | Maximum D-value | : | 7,99 | kN |
|------|---|---|------|-----|
| 1.4. | Maximum vertical load S at the coupling point | : | 75 | kg |
| 1.5 | Maximum load U at the fifth wheel | : | | ton |

| | coupling point | | |
|------|-----------------|---|--------|
| 1.6. | Maximum V-value | : | kN |

| 1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles | : | See fitting instructions |
|---|---|--------------------------|
|---|---|--------------------------|

| 1.8 | Information on the fitting of special towing | : | See fitting instructions |
|-----|--|---|--------------------------|
| | brackets or mounting plates | | _ |

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.

