

NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1551*00

Reason for extension:

SECTION I

	believ.		
0.1.	Make (trade name of manufacturer)	:	Bosal
0.2.	Type and general commercial description(s)	:	026421
0.3.	Means of identification of type marked on the component	:	Approval number
0.3.1.	Location of that marking	:	On type plate
0.5.	Name and address of manufacturer	:	Bosal postbus 168 4920 AD Made Nederland
0.7.	In the case of components and separate technical units, location and method of affixing of the EEC type approval mark	:	On type plate
0.8.	Address(es) of assembly plant(s)	:	See information document (annex III, item 0.8)

Type-approval number: e4*94/20*1551*00

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76

8218 NX Lelystad

M.L. Veenstra

3. Date of test report : 29-09-2000

4. Number of test report : RDW-94/20-1140

5. Remarks (if any) : See Appendix I

6. Place : Zoetermeer

7. Date : 12.0KT 2000

8. Signature : ////

9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.

- Application form relating to annex III and annexed drawings
- Drawings and instructions for attachment
- Fitting instructions
- Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No: e4*94/20*1551*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.	Additional information				
1.1.	Class of the type of coupling	:	A50-X		
1.2.	Categories or types of vehicles for which the device is designed or restricted	:	See fitting instructions		
1.3.	Maximum D-value	:	6,73	kN	
1.4.	Maximum vertical load S at the coupling point	:	50	kg	
1.5	Maximum load U at the fifth wheel coupling point	:		ton	
1.6.	Maximum V-value	:		kN	
1.7.	Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles	:	See fitting instructions		
1.8	Information on the fitting of special towing brackets or mounting plates	:	See fitting instructions		

5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.