



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1555*00

Reason for extension:

SECTION I

Make (trade name of manufacturer) Le Rapide 0.1. Type and general commercial description(s) 026501 0.2. : Approval number Means of identification of type marked on the 0.3. component : On type plate 0.3.1. Location of that marking : Bosal Le Rapide Name and address of manufacturer 0.5. Rue de Reims F-51490 Beine Nauroy France In the case of components and separate technical: On type plate 0.7. units, location and method of affixing of the EEC type approval mark : See information document Address(es) of assembly plant(s) 0.8. (annex III, item 0.8)

Type-approval number: e4*94/20*1555*00

SECTION II

See Appendix I Additional information (where applicable) 1.

Technical service responsible for carrying out 2. the tests

RDW

Testbaan|Centrum Talingweg 76

8218 NX Lelystad

M.L. Veenstra

: 11-09-2000 Date of test report 3.

RDW-94/20-1282 Number of test report 4.

See Appendix I Remarks (if any) 5.

Zoetermeer 6. Place

05.0KI 2000

7. Date 8. Signature

- The index to the information package lodged with the competent authority that has granted 9. type-approval, which may be obtained on request, is attached.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I to EEC type-approval certificate No: e4*94/20*1555*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.	Additional information			
1.1.	Class of the type of coupling	:	A50-X	
1.2.	Categories or types of vehicles for which the device is designed or restricted	:	See fitting instructions	
1.3.	Maximum D-value	:	8,60	kN
1.4.	Maximum vertical load S at the coupling point	:	75	kg
1.5	Maximum load U at the fifth wheel	:		ton
1.6.	coupling point Maximum V-value	:		kN
1.7.	Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles	:	See fitting instructions	
1.8	Information on the fitting of special towing brackets or mounting plates	:	See fitting instructions	

Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10. 5.