



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type-approval
- extension of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*1603*00

Reason for extension:

SECTION I

0.1. Make (trade name of manufacturer) Le Rapide 0.2. Type and general commercial description(s) 026751 0.3. Means of identification of type marked on the : Type approval number component 0.3.1. Location of that marking On type plate 0.5. Name and address of manufacturer Bosal Le Rapide Rue de Reims F-51490 Beine Nauroy France 0.7. In the case of components and separate technical: On type plate units, location and method of

affixing of the EEC type approval mark

Address(es) of assembly plant(s) : See information document

(annex III, item 0.8)

0.8.

Type-approval number: e4*94/20*1603*00

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum Talingweg 76

8218 NX Lelystad

3. Date of test report

10-04-2003

4. Number of test report

RDW-94/20-1297

5. Remarks (if any)

: See Appendix I

6. Place

Zoetermeer

7. Date

10-04-2003

8. Signature

J.P.M. Laumen

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No : e4*94/20*1603*00 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1	Additional	+~	
1	Апппони		пинки

1.1.	Class of the type of coupling	:	A50-X
------	-------------------------------	---	-------

1.2.	Categories or types of vehicles for which	:	See fitting instructions
	the device is designed or restricted		-

1.3.	Maximum D-value	:	6,44	kN
1.4.	Maximum vertical load S at the coupling point	:	70	kg
1.5	Maximum load U at the fifth wheel	:		ton
1.6.	coupling point Maximum V-value	:		kN

type to the drawings give by th information	ons for attachment of the coupling e vehicle and photographs or of the fitting points at the vehicle ne manufacturer; additional on if the use of the coupling type is to special types of vehicles	:	See fitting instructions
--	--	---	--------------------------

- 1.8 Information on the fitting of special towing : See fitting instructions brackets or mounting plates
- 5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par. 5.10.

