



NEDERLAND (THE NETHERLANDS)



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning:

- type approval
- extension of type-approval
- refusal of type approval
- withdrawal of type-approval-

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4*94/20*2286*01

Reason for extension: Technical modifications

SECTION I

0.1. Make (trade name of manufacturer) Bosal 0.2. Type and general commercial description(s) : 032061 0.3. Means of identification of type marked on the : Type approval number component 0.3.1. Location of that marking On type plate 0.5. Name and address of manufacturer **Bosal** Tweede industrieweg 6 4921 XH Made, the Netherlands 0.7. In the case of components and separate technical: On type plate units, location and method of affixing of the EEC type approval mark

0.8. Address(es) of assembly plant(s)

: See information document

(annex III, item 0.8)

Type-approval number: e4*94/20*2286*01

SECTION II

1. Additional information (where applicable) : See Appendix I

2. Technical service responsible for carrying out

the tests

RDW

Testbaan|Centrum

Talingweg 76 8218 NX Lelystad

3. Date of test report : 10-07-2003

03-09-2003

4. Number of test report : RDW-94/20-3380

RDW-94/20-3432

5. Remarks (if any) : See Appendix I

6. Place : Zoetermeer

7. Date : 03-09-2003

8. Signature

J.P.M. Laumen

- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request.
 - Application form relating to annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Test report as mentioned in item 4.

Appendix I

to EEC type-approval certificate No : e4*94/20*2286*01 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

_			_
1	Additional	intom	antina
	Addillonal	111111111	121111111

	C1	1 70 77
1.1.	Class of the type of coupling	: A50-X
1.1.	Class of the type of coupling	. /1JU-/1

1.2.	Categories or types of vehicles for which	:	See fitting instructions
	the device is designed or restricted		

1.3.	Maximum D-value	:	11,29		kN
1.4.	Maximum vertical load S at the coupling point	:	80	kg	
1.5	Maximum load U at the fifth wheel coupling point	:		ton	
1.6.	Maximum V-value	:		kN	

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle give by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles	See fitting instructions
---	--------------------------

- 1.8 Information on the fitting of special towing : See fitting instructions brackets or mounting plates
- 5. Remarks: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.

